







WHEELS WITH THICK "TR" POLYURETHANE AND ALUMINIUM CENTRE

-  100-250 mm
-  95 Shore A
-  350-1000 daN
4 km/h
-  280-800 daN
6 km/h
-  270-380 daN
-  -20 / +80 °C



Technical features

Tyre: very thick "TR" polyurethane, hardness 95 Shore A; excellent rolling resistance and elasticity, highly resistant to wear and tear.

Centre: made of cast aluminium.

Hub with shielded ball bearings with interference assembly in the seats obtained by centre moulding; also available without bearings.

Uses

Designed to improve trolleys' handling under heavy loads on uneven surfaces.

The thick tread guarantees: excellent ability to overcome obstacles, reduced fatigue when pushing the trolley, excellent performance in presence of mechanical handling or mixed manual-mechanical handling, excellent performance over time, even at high speeds (up to 12 km/h).

Examples of recommended applications: trolleys for indoor handling in the logistics and automotive industry, electrical pallet trucks.

Environments of use

Designed for industrial environments, even in presence of alcohols, glycols, hydrocarbons. Not recommended in areas with organic acids and mineral acids, base solutions and saturated vapour.

WEAK ACIDS		WEAK BASES	
STRONG ACIDS		STRONG BASES	
WATER		HYDROCARBONS	
ALCOHOL		SOLVENTS	



For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.

Floors

Suitable for all types of industrial floors, except unpaved; it easily overcomes obstacles.



Force required to push or tow a wheel

 	100 kg	300 kg	400 kg	500 kg	650 kg	800 kg
100 mm	2.5	5.5	----	----	----	----
125 mm	2.4	5.3	----	----	----	----
160 mm	1.8	4.7	5.8	7	11	----
180 mm	1.5	4.4	5.6	6.5	10	----
200 mm	1.2	4	5.4	6.2	9	12

For each load and diameter, the table indicates the force (in daN) needed to push or tow a single wheel at the constant speed of 4 km/h on smooth flooring. For manual handling of a 4-wheeled trolley we recommend diameters that have values < 5 daN, for frequent handling we recommend diameters with values < 3 daN.

Available with brackets



Medium-heavy duty brackets P














Maximum carrying capacity 750 daN - available diameters 100-250 mm
Top plate fitting. Available with front brake and adjustable rear brake.




Electrowelded brackets EE MHD

Maximum carrying capacity 800 daN - available diameters 100-200 mm
Top plate fitting. Available with adjustable rear brake.


















															
mm	mm	kg	CODE	kg	CODE	mm	mm	mm	mm	daN	daN	daN	daN		
100	40	0.46	652302	0.38	654302	15	40	32	9	500	270	350	280		
125	40	0.76	652303	0.41	654303	20	50	47	14	650	280	450	360		
160	50	1.18	652304	0.95	654304	20	58	47	14.5	900	320	700	560		
180	50	1.44	652305	1.21	654305	20	58	47	14	950	335	750	600		
200	50	1.76	652306	1.52	654306	20	58	47	14	1000	350	800	640		
250	50	2.40	652308	2.10	654308	20	55	52	15	1200	380	1000	800		

Medium-heavy duty brackets P - max carrying capacity 750 daN



- 1) Plate: galvanised colonial platesteel
 - 2) Fork: galvanised colonial platesteel
 - 3) Ball race ring: galvanised colonial platesteel
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: steel bolt in grade 8.8 steel and steel nut
- Available with total front foot brake


																
mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN	daN
100	40	1.33	655302	0.83	655412	1.50	655502	138	100x85	80x60	9	46	123	350	280	

Options available to order:



Footguard
for brackets
M-P


Medium-heavy duty brackets P - max carrying capacity 750 daN



- 1) Plate: galvanised colonial steel plate
 - 2) Fork: galvanised colonial steel plate
 - 3) Ball race ring: galvanised colonial steel plate
 - 4) Dust seal: orange polyamide
 - 5) Swivel actions: double ball ring with grease lubrication
 - 6) King pin: steel bolt in grade 8.8 steel and steel nut
- Available with adjustable total rear foot brake

mm		kg		kg		kg		mm		mm		mm		mm		daN	
mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	mm	4 km/h	6 km/h
125	40	2.30	655303	1.63	655403	2.83	655503	170	140x110	105x80	11	70	126			450	360
160	50	3.53	655310	2.04	655414	4.10	655504	205	140x110	105x80	11	70	126			700	560
180	50	3.78	655305	2.36	655415	4.35	655505	228	140x110	105x80	11	70	126			750	600
200	50	4.22	655316	2.76	655416	4.82	655506	250	140x110	105x80	11	70	126			750	600
250	50	4.84	655318	3.74	655418	5.54	655508	298	140x110	105x80	11	66	126			750	600

Electrowelded brackets EE MHD - max carrying capacity 800 daN



- 1) Plate: forged steel with integrated pin
 - 2) Fork: deep-drawn legs electro-welded to the flange
 - 3) Swivel actions: axial ball bearing and tapered roller bearing
 - 4) Grease nipple
 - 5) Anti-loosening system nut
- Available with adjustable total rear foot brake

mm		kg		kg		kg		mm		mm		mm		mm		daN	
mm	mm	kg	CODE	kg	CODE	kg	CODE	mm	mm	mm	mm	mm	mm	mm	mm	4 km/h	6 km/h
100	40	3.36	655602	2.38	655702	4.24	655802	170	135x110	105x80	11	51	157			350	280
125	40	3.68	655603	2.70	655703	4.56	655803	182	135x110	105x80	11	51	157			450	360
160	50	4.18	655614	3.19	655714	5.06	655814	215	135x110	105x80	11	60	157			700	560
180	50	4.56	655605	3.58	655705	5.45	655805	242	135x110	105x80	11	70	157			750	600
200	50	4.88	655606	3.90	655706	6.22	655806	252	135x110	105x80	11	70	157			800	640

Options available to order:



Directional lock for P brackets d. 150-200 mm



Directional lock for brackets EE MHD - EE HD - EED MHD: see page 332



Footguard for brackets M-P