

## ABRASAND /10

SANDBLASTING HOSE



### APPLICATION

Delivery hose, sand and bead blasting application

### TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

### REINFORCEMENT

High strength synthetic plies

### COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

### WORKING TEMPERATURE

-40°F + 158°F

### SPECIFICATIONS

DIN 53516 70 ± 5mm<sup>3</sup>

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,44	10	150	30	450	40
16	5/8	30	1 3/16	0,59	10	150	30	450	40
19	3/4	30	1 3/16	0,50	10	150	30	450	40/61
19	3/4	33	1 5/16	0,66	10	150	30	450	40/61
25	1	40	1 9/16	0,88	10	150	30	450	40/61
30	1 3/16	45	1 25/32	1,02	10	150	30	450	40/61
32	1 1/4	48	1 7/8	1,16	10	150	30	450	40/61
38	1 1/2	54	2 1/8	1,33	10	150	30	450	40/61
40	1 9/16	60	2 3/8	1,83	10	150	30	450	40/61
51	2	71	2 13/16	2,20	10	150	30	450	40/61
60	2 3/8	80	3 3/16	2,53	10	150	30	450	40/61
80	3 5/32	105	4 1/8	4,18	10	150	30	450	40/61
90	3 1/2	115	4 17/32	4,63	10	150	30	450	40/61
102	4	127	5	5,17	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING

