








Hose in PU with embedded galvanised steel spiral for suction and delivery, food liquids and food oils.


- 
SMOOTH SURFACES *****


- 
FLEXIBILITY *****


- 
ABRASION RESISTANCE *****

- 
TEMPERATURE RANGE -40°C +90°C
32°F +32°F

- 
CHEMICAL RESISTANCE PU table

- 
CRUSHING RESISTANCE ***

- 
PHT HALATE FREE *****
TPHF

- 
FOR FOOD Suitable for contact with foodstuff according to the Declaration of Conformity

Ø I.D.	Ø I.D.	Ø O.D.	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	VACUUM 23°C	SPIRAL PITCH	Ø SPIRAL	COIL LENGTH	AVAILABILITY
inch	mm	mm	g/m	mm	bar	m h2o	mm	mm	m	
	20	28.5	410	80	7	9	7.5	1	30	IN STOCK
	25	33.5	520	100	7	9	7.5	1	30	IN STOCK
	30	39.2	620	120	7	9	8	1	30	IN STOCK
	40	49.4	900	160	6	8	8.5	1.2	30	IN STOCK
	50	60.4	1160	200	6	8	9.5	1.5	30	IN STOCK
	60	70	1440	240	6	8	10.5	1.5	30	IN STOCK
	70	80	1650	300	5	8	12.5	1.8	30	IN STOCK
	75	85	1730	320	5	7	14	1.8	30	IN STOCK
	80	90	1800	340	4	7	14	1.8	30	IN STOCK
	100	114	3250	400	3	7	15	2.5	30	IN STOCK
	102	116	3300	420	3	7	15	2.5		ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.